

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

1. (Previously Amended) A wireless communications device,  
comprising:

a first transceiver having a first receiver and a first transmitter;

a first antenna coupled to the first receiver;

5 a second transceiver having a second receiver and a second  
transmitter;

a second antenna coupled to the second receiver,

the first and second transmitters connectable at the same time to  
the same one of either of the first and second antennas.

10  
C1  
Claim 2 (Canceled).

15 3. (Previously Presented) The wireless communications device of  
Claim 1, the first and second transmitters disconnectable from the same one of  
the first and second antennas.

20 4. (Previously Presented) The wireless communication device of  
Claim 1, the first receiver is a CDMA receiver, the first transmitter is a CDMA  
transmitter, the second receiver is a TDMA receiver, the second transmitter is a  
TDMA transmitter.

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

5. (Previously Presented) The wireless communication device of Claim 1, the first antenna is an internal antenna, the first transmitter coupled to the second antenna, the second antenna is an external antenna.

5

6. (Previously Presented) The wireless communication device of Claim 1, a switch coupling the first and second transmitters and the second receiver to the same one of the first and the second antennas.

10

7. (Previously Presented) The wireless communications device of Claim 1, a processor coupled to the first and second transceivers, a display and input/outputs coupled to the processor.

15

Claim 8 (Canceled).

Claim 9 (Canceled).

20

10. (Previously Presented) A method in a wireless communications device having a first transceiver and a second transceiver, comprising:

25

receiving an uncompressed CDMA signal with a first receiver of the first transceiver;

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

receiving a second signal with a second receiver of the second transceiver at the same time the first receiver is receiving the uncompressed CDMA signal.

5

11. (Previously Presented) The method of Claim 10,  
receiving the second signal with the second receiver operating in a non-continuous reception mode at the same time the first receiver is receiving the uncompressed CDMA signal.

10

U  
12. (Previously Presented) The method of Claim 10,  
the first receiver is CDMA receiver, the second receiver is a GSM receiver,

15

receiving a downlink signal with the GSM receiver at the same time the CDMA receiver is receiving the uncompressed CDMA signal.

20

13. (Previously Presented) The method of Claim 10,  
the first receiver is CDMA receiver, the second receiver is a TDMA receiver,  
receiving a downlink signal with the TDMA receiver at the same time the CDMA receiver is receiving the uncompressed CDMA signal.

25

14. (Previously Presented) The method of Claim 10,

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

receiving a second uncompressed downlink signal with the second receiver operating in a continuous reception mode at the same time the first receiver is receiving the uncompressed CDMA signal.

5

15. (Previously Presented) The method of Claim 10,

the first receiver coupled to a first antenna,

the second receiver coupled to a second antenna different than the first antenna,

10

the first transceiver includes a first transmitter, the second transceiver includes a second transmitter,

connecting the first transmitter and the second transmitter to the same one of the first and second antennas at the same time.

15

16. (Previously Presented) A method in a wireless communications device having a first transceiver, the method comprising:

receiving a first signal with a first receiver of the first transceiver,  
the first receiver coupled to a first antenna;

20

transmitting a second signal with a first transmitter of the first transceiver at the same time the first receiver is receiving the first signal.

the first transmitter coupled to a second antenna different than the first antenna.

25

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

17. (Previously Presented) The method of Claim 16, receiving the first signal with the first receiver includes receiving an uncompressed CDMA downlink signal.

5

Claim 18 (Canceled).

Cl

Claim 19 (Canceled).

10

20. (Currently Amended) A method in a wireless communications device having a first transceiver and a second transceiver, comprising:

transmitting a first signal with a first transmitter of the first transceiver operating in a continuous spread spectrum transmission mode,

15

the first transmitter coupled to a first antenna;

receiving a second signal with a second receiver of the second transceiver at the same time the first transmitter is transmitting the first signal,

the second receiver coupled to a second antenna different than the first antenna.

20

21. (Original) The method of Claim 20,

the first transmitter is CDMA transmitter, the second receiver is a TDMA receiver,

25

transmitting an uplink signal with the CDMA transmitter;

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

receiving the second signal with the TDMA receiver at the same time the CDMA transmitter is transmitting the uplink signal.

5

22. (Original) The method of Claim 20,

transmitting an uncompressed uplink signal with a first transmitter operating in a continuous transmit mode;

receiving the second signal with the second receiver at the same time the first transmitter is transmitting the uncompressed uplink first signal.

10

C1

23. (Previously Presented) The method of Claim 20,

the first transmitter is CDMA transmitter, the second receiver is a TDMA receiver,

15

transmitting an uncompressed uplink signal with the CDMA transmitter;

receiving the second signal with the TDMA receiver at the same time the CDMA transmitter is transmitting the uncompressed uplink signal.

20

24. (Previously Presented) A method in a wireless communications device having a first transceiver and a second transceiver, the method comprising:

transmitting with a first transmitter of the first transceiver;

25

transmitting with a second transmitter of the second transceiver at the same time that the first transmitter is transmitting;

LEYH ET AL.  
"Multi-Mode Communications Device With  
Continuous Mode ..."  
Atty. Docket No. CS11235

Appl. No. 10/027,650  
Confirm. No. 1167  
Examiner T. Ewart  
Art Unit 2684

receiving with one of a first receiver of the first transceiver and a second receiver of the second transceiver at the same time the first and second transmitters are transmitting.

5

25. (Previously Presented) The method of Claim 24, receiving includes receiving an uncompressed continuous signal.

Cl

10

26. (Previously Presented) A method in a wireless communications device having a first transceiver and a second transceiver, the method comprising:

receiving with a first receiver of the first transceiver;

15

receiving with a second receiver of the second transceiver at the same time that the first receiver is receiving;

transmitting with one of a first transmitter of the first transceiver and a second transmitter of the second transceiver at the same time the first and second receivers are receiving.

20

27. (Previously Presented) The method of Claim 26, receiving includes receiving an uncompressed continuous signal.

---